

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup>:</b> <b>C11D 17/00, 3/18</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 97/00934</b> <b>(43) International Publication Date:</b> 9 January 1997 (09.01.97)
<b>(21) International Application Number:</b> PCT/AU96/00373 <b>(22) International Filing Date:</b> 21 June 1996 (21.06.96)  <b>(30) Priority Data:</b> 9512900.3                      23 June 1995 (23.06.95)                      GB  <b>(71) Applicant:</b> R & C PRODUCTS PTY. LIMITED [AU/AU]; 33 Hope Street, Ermington, NSW 2115 (AU).  <b>(72) Inventor:</b> SILVESTER, Raymond, Neville; 14 Coomalie Avenue, Castle Hill, NSW 2154 (AU).  <b>(74) Agent:</b> F.B. RICE & CO.; 28A Montague Street, Balmain, NSW 2041 (AU).		<b>(81) Designated States:</b> AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.</i>
<b>(54) Title:</b> AEROSOL CLEANING COMPOSITIONS  <b>(57) Abstract</b>  A cleaning composition being an oil-in-water emulsion in aerosol form characterised in that sufficient of the propellant is retained in the emulsion on discharge to a surface such that the retained propellant boils to create a sustained bubbling action in the absence of foaming on the surface. The cleaning composition comprises an oil-in-water emulsion containing (a) 2 to 60 % w/w in total amount of one or more hydrocarbon propellants such that the propellants substantially form a part of the oil phase when the composition is formulated; (b) 2 to 50 % w/w in total amount of one or more surfactants; (c) 0.1 to 30 % w/w in total amount of one or more water-immiscible organic compounds; (d) 0.5 to 40 % w/w in total amount of one or more water-miscible organic coupling agents; and (e) 10 to 70 % w/w of water.		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

## Aerosol Cleaning Compositions

### Technical Field

5 This invention relates to cleaning compositions and in particular to compositions in aerosol form that are useful in cleaning a wide range of surface types including textiles such as clothing, fabrics and carpets and hard surfaces such as glass, metal, ceramics, porcelain, synthetic plastics and vitreous enamel.

### Background Art

10 The prior art is replete with a variety of aerosol compositions for use in cleaning many surface types. Basically, these compositions may be divided into two groups, namely those that are solvent-based and those that are water-based. Both of these groups suffer from shortcomings which desirably should be overcome or at least improved.

15 In the case of solvent-based compositions, the prime concerns are environmental and undesirable solvent odour.

In the case of water-based compositions, the prime concern is cleaning performance, particularly in relation to grease, wax and oil-based soils.

20 It would therefore be an advance in the art to be able to provide a water-based composition with enhanced cleaning performance, desirably with a grease, wax and oil-based soil cleaning performance akin to the solvent-based compositions.

25 The present inventors have surprisingly found that one way of meeting this performance requirement for a water-based composition occurs when certain oil-in-water emulsions are formed. These emulsions are characterised by a substantial proportion or all of the aerosol propellant forming a part of the oil-phase when the composition is fully formulated.

### Disclosure of Invention

30 Accordingly, the present invention consists in a cleaning composition comprising in aerosol form an oil-in-water emulsion containing:

- (a) one or more hydrocarbon propellants in a total amount of from 2 to 60% w/w, wherein the propellants substantially form a part of the oil phase when the composition is formulated;
- (b) one or more surfactants in a total amount of from 2 to 50% w/w;
- 35 (c) one or more water-immiscible organic compounds in a total amount of from 0.1 to 30% w/w;

(d) one or more water-insoluble organic coupling agents in a total amount of from 0.5 to 40% w/w; and

(e) water in an amount of from 10% w/w to 70% w/w;

characterised in that sufficient of the propellant is retained in the emulsion on discharge to a surface such that the retained propellant boils to create a sustained bubbling action in the absence of foaming on the surface.

As used in this specification, all percentages are w/w with respect to the active material, unless otherwise indicated.

#### Modes for Carrying Out the Invention

It is believed that the cleaning performance of the compositions of this invention derives from at least two factors. Firstly the solvent action of the propellant retained in the oil phase when the composition on discharge contacts the soil. Secondly, the physical agitation caused by the propellant in the oil phase boiling off to the atmosphere. This is the belief of the inventors, although it will be appreciated that in considering the nature of this invention, this belief is non-binding and should not in any way be construed as a limitation of the scope of the invention.

The boiling off of the propellant from the surface onto which a composition of the invention is discharged is characterised by a bubbling action on the surface. This bubbling action could also be described as "sizzling". In general terms the bubbles are fast breaking and do not persist to create a foam.

The bubbling action is sustained, being generally characterised by an initial vigorous action for up to about 15 seconds then a continuous, less vigorous phase for up to 1 minute or more.

It is, however, preferred that no or minimal amounts of foam are formed. In this way, it will be readily apparent to a consumer using a composition of the invention that cleaning is occurring as the bubbling action will be visually apparent.

Desirably, the compositions on discharge will be further characterised presenting as a wet spray in appearance. In this form the composition "wets out" the stain.

The bubbling action contributes significantly to the broad spectrum cleaning performance of the compositions of the invention by providing a physical lifting action. In particular, in the compositions of the invention, the retained propellant is released in the form of bubbles which relatively

quickly break releasing propellant to the atmosphere. The sustained nature of this bubbling action provides a prolonged cleaning action.

It is important to note that compositions in the prior art do not display the sustained bubbling action on account of the propellant rapidly flashing off to the atmosphere.

The compositions of the present invention are water-based although it is evident that their cleaning performance is equivalent to or exceeds solvent-based compositions. This is indeed surprising in view of prior art water-based compositions.

#### **Nature of the Emulsion**

In the compositions of the invention a concentrate which includes (b), (c), (d) and (e) will be formed. Propellant is added to this concentrate to create compositions of the invention.

Prior to the addition of propellant, the concentrate desirably is a stable oil-in-water emulsion, preferably a substantially clear microemulsion.

It is, however, within the scope of the invention to utilise a concentrate that is not a fully stable or clear oil-in-water emulsion. For emulsions of this type, it is a requirement that upon addition of propellant, an oil-in-water emulsion is formed such that sufficient of the propellant is retained in the emulsion on discharge to a surface so that the retained propellant boils to create a bubbling action on the surface. Such an emulsion may be clear or characterised by a slight haziness through to a milky liquid to the presence of some separate oil layer.

In the fully formulated compositions of the invention, ie when the propellant is added to the concentrate, it is preferred that substantially all of the propellant is taken up in the oil-phase to form an oil-in-water emulsion. This emulsion is desirably a stable clear microemulsion. Emulsions with some separate oil phase, however, are acceptable providing that the separate oil phase portion re-emulsifies on shaking and sufficient of the propellant is retained in the emulsion on discharge to a surface such that the retained propellant boils to create a bubbling action on the surface.

#### **(a) Propellant**

One or more hydrocarbon propellants are used in the compositions of the invention in a total amount from 2 to 60% w/w. Amongst the hydrocarbon propellants that may be used are acetylene, methane, ethane, ethylene, propane, propene, n-butane, n-butene, iso-butane, iso-butene,

pentane, pentene, iso-pentane and iso-pentene. Mixtures of these propellants may also be used.

Indeed, it should be noted that commercially available propellants typically contain a number of hydrocarbon gases. For example, unodourised commercial butane (available from Boral Gas) contains predominantly n-butane and some iso-butane along with small amounts of propane, propene, pentane and butene.

Preferred propellants include propane, n-butane, iso-butane, pentane and iso-pentane, whilst most preferred are propane, n-butane and iso-butane.

Broadly, the concentration of propellant will be from 2 to 60% w/w, generally the concentration will be from 5 to 50% w/w; preferably from 10 to 30% w/w.

Particularly preferred are mixtures of propane, n-butane and iso-butane.

The person skilled in the art will appreciate that the pressure in an aerosol package will be determined by the propellant or mixture of propellants. This pressure will have a determining effect on spray rate. Hence for any particular valve system, varying the propellant or propellant mixture will allow for the selection of a desired spray rate.

Likewise, for a particular propellant or propellant mixture, it is possible to select a valve and actuator system to achieve a desired rate.

As previously mentioned, sufficient of the propellant must be retained in the emulsion on discharge so to create the boiling action. It has been found that approximately 4 to 6% w/w of propellant may be retained in the emulsion immediately after discharge onto a surface. It must be appreciated, however, that the amount of retained propellant is difficult to measure accurately. The amount recited is therefore for guidance only. The bubbling action is nevertheless an important characteristic of the composition of the invention. In use on oils such as dirty sump oil stains, it is visually evident that the bubbling action actually lifts the stain away from a fabric surface.

(b) Surfactants

One or more surfactants are included in a total amount of from 2 to 50% w/w, preferably from 5 to 25% w/w. Either nonionic, amphoteric, anionic or cationic surfactants may be used, although nonionic and/or amphoteric surfactants are preferred. The surfactants function primarily in

the formation of the emulsion. Desirably, the surfactants also contribute to cleaning.

When more than one surfactant is used, an individual surfactant component may be in a concentration as low as 0.1 to 0.5% w/w. For example, sodium lauroyl sarcosinate may be used in a concentration of 0.2% w/w as a corrosion inhibitor. In a further example, Surfadone LP300 in a concentration of 0.5% w/w may be used to improve wetting and stain removal. They will, however, participate in the oil-in-water emulsion.

Examples of surfactants that may be used are as follows:

- 10 **Nonionic surfactants** - sorbitan fatty acid ester ethoxylates, glycerol fatty acid ester ethoxylates, sorbitan fatty acid esters, glycerol fatty acid esters, coconut monoethanolamide ethoxylates, tall oil ethoxylates, polypropylene glycol ethoxylates, fatty acid alkanolamides such as coconut mono- and diethanolamide, fatty alcohol ethoxylates and propoxylates, amine oxides, n-alkyl pyrrolidones, alkyl polysaccharides such as sucrose esters and alkyl polyglycosides, alkyl phenol ethoxylates, ethoxylated castor oil, fatty acid ethoxylates, fatty amine ethoxylates, polyglycerol fatty acid esters.
- 15 **Anionic surfactants** - sodium lauryl ether sulfate, triethanolamine lauryl sulphate, magnesium lauryl sulfate, sulfosuccinate esters, ammonium lauryl sulfate, alkyl sulfonates, sodium lauryl sulfate, sodium alpha olefin sulfonates, alkyl sulfates, sulfated alcohol ethoxylates, sulfated alkyl phenol ethoxylates, sodium xylene sulfonate, alkylbenzene sulphonates such as triethanolamine dodecylbenzene sulfonate, sodium dodecylbenzene sulfonate, calcium dodecylbenzene sulfonate, xylene sulfonic acid, dodecylbenzene sulfonic acid, N-alkoyl sarcosinates such as sodium lauroyl sarcosinate, dialkylsulfosuccinates, N-alkoyl sarcosines such as lauroyl sarcosine, alkyl ether carboxylates, soaps including sodium, potassium, magnesium, calcium, alkanolamine and amine soaps.
- 20 **Amphoteric surfactants** - betaines, n-alkyl pyrrolidones (because it has a resonance structure, it may behave as a zwitterionic substance), imidazolines.
- 25 **Cationic surfactants** - quaternary ammonium compounds including alkyl dimethyl benzyl ammonium chloride, dialkyl dimethyl ammonium chloride, alkyl trimethyl ammonium chloride or bromide, salts of organic or inorganic acids with fatty amines and fatty amine ethoxylates.
- 30

Mixtures of surfactants types may be used such as nonionic and anionic surfactants. A proprietary mixture of this type is Monamulse DL 1273 available from Mona Industries, Inc.

(c) Water-Immiscible Organic Compound

5       The primary function of this component is to suppress the generation of foam on discharge of the aerosol. Such a property, as previously explained, is important to the performance of the compositions of the invention, since what is required is a bubbling action on the surface, rather than a foam.

10       Preferred water immiscible organic compounds, however, will usually have a secondary cleaning functionality through their solvency properties.

      One or more water immiscible organic compounds are included in the composition in a total amount from 0.1 to 30% w/w, preferably 0.5% to 15 30% w/w, most preferably 2% w/w to 20% w/w.

      In the lower end of the concentration range, silicone antifoams may be used such as Dow Corning Antifoam A.

      Examples of water immiscible organic compounds include - liquid n-paraffins, liquid iso-paraffins, cycloalkanes, naphthene-containing solvents, 20 white spirit, kerosene, aromatic solvents, mineral turpentine, ester solvents, silicone solvents or oils, terpenes, fatty acids, paraffin waxes, linear alkyl benzene, dialkyl phthalates, C<sub>5</sub> - C<sub>11</sub> alcohols and fatty alcohols. Specific examples of these are as follows:

      liquid n-paraffins - Norpar 12, Norpar 13 and Norpar 15 (available 25 from Exxon)

      liquid iso-paraffins - Isopar G, Isopar H, Isopar L, Isopar M and Isopar V (available from Exxon)

      naphthene-containing solvents - Exxsol D40, Exxsol D60, Exxsol D80, Nappar 10 (available from Exxon)

30       ester solvents - such as alkyl acetates, examples being Exxate 1000, Exxate 1300 (available from Exxon), and Coasol (available from Chemoxy International).

      silicone solvents or oils - Dow Corning 244, 245, 344 and 345 fluids.

      terpenes - eucalyptus oil, cineole, orange oil, limonene.

35       fatty amines - soya amines, tallow amines, cocoamines.



fatty acids - caprylic acid, caproic acid, capric acid, lauric acid, myristic acid, palmitic acid, stearic acid, behenic acid, oleic acid.

fatty alcohols - octanol, dodecanol, lauryl alcohol, myristyl alcohol, cetyl alcohol, stearyl alcohol, cetostearyl alcohol, oleyl alcohol.

5 aromatic solvents - toluene, benzene, xylene.

Preferred water immiscible organic compounds are liquids at room temperature. Particularly preferred are hydrocarbon solvents, especially those that are good grease solvents. Most preferred are hydrocarbon solvents having a low solvent odour such as n-paraffins and iso-paraffins.

10 (d) Water-Miscible Organic Coupling Agent

One or more water miscible organic coupling agents are included in a total amount of from 0.5 to 40% w/w, preferably 5 to 30% w/w.

The coupling agent primarily functions to couple the propellant to the water and the water immiscible organic compound to the water. This  
15 assists in the formation of the emulsion and the retention of the propellant after discharge of compositions of the invention. The coupling agent also functions to couple the surfactant to the water, so as to prevent insolubility and/or gelling when it occurs.

A secondary function is to provide some solvency for cleaning.

20 Amongst the compounds that may be used are:-

low molecular weight alcohols such as methanol, ethanol, n-propanol, iso-propanol, n-butanol and iso-butanol;

glycol ethers such as ethylene glycol monobutyl ether, dipropylene glycol monomethyl ether, propylene glycol monomethyl ether and  
25 diethylene glycol monobutyl ether;

glycols such as propylene glycol, hexylene glycol and ethylene glycol;

polyglycols such as PEG200 and PEG6000;

polypropylene glycols;

30 polyols such as glycerol, sorbitol, pentaerythritol and mannitol;

low molecular weight ketones such as acetone; and

N-methyl pyrrolidone.

Preferred are the low molecular weight alcohols, particularly ethanol or iso-propanol, most preferred is ethanol.

(e) Water

The water is included in the compositions of the invention in an amount of from 10 to 70% w/w, preferably 25 to 55% w/w.

Desirably the water is purified before use and may be deionised or distilled.

In addition to the essential components (a) to (e), a range of optional components may be included. The inclusion of the components may be specific to a particular composition type or may be to meet a particular compositional need or consumer requirement.

10 (f) Optional Components

- (i) Surfactant additives - These may be included to enhance cleaning and washout performance. Examples include good wetting agents, dispersing agents and the like. Specific examples include Surfadone LP 300 (n-dodecyl-2-pyrrolidone available from ISP) and Surfadone LP 100 (n-octyl-2-pyrrolidone); as good wetting agents, sodium lauryl ether sulphate as a dispersing agent for inorganic soil.
- 15 (ii) Alkaline builder salts such as sodium carbonate, sodium sesquicarbonate, sodium tripolyphosphate, tetrasodium pyrophosphate, tetrapotassium pyrophosphate, zeolites, sodium hexametaphosphate.
- 20 (iii) Sequestering, complexing agents or water softening agents such as EDTA and its salts, sodium citrate, sodium gluconate, sodium glucoheptonate, phosphonates, DTPA and its salts, NTA and its salts.
- 25 (iv) pH control, buffering or adjusting agents such as sodium bicarbonate, ammonium bicarbonate.
- (v) Perfumes.
- (vi) Dyes.
- (vii) Preservatives.
- (viii) Soil suspending or anti-redepositing agents.
- 30 (ix) Soil release or anti-resoiling agents such as Zonyl 7950, Zelan 338 (available from Dupont), Repel-o-Tex QCJ and QCX (available from Rhone-Poulenc)
- (x) Corrosion inhibitors such as sodium lauroyl sarcosinate, AMP regular, sodium nitrite, QAI 50% - 2 hydroxy propamine nitrite
- 35 (available from Enviro Systems USA).

- (xi) Co-surfactants (water immiscible coupling agents) - including C<sub>5</sub>-C<sub>18</sub> alcohols,
- (xii) Organic and/or inorganic acids - particularly in use for compositions of the invention which are toilet cleaners. Such compositions will usually require the use of synthetic plastic aerosol containers.
- (xiii) Thickening agents - particularly to retard release of propellant from the bubbling surface. May also be used for particular compositional requirements such as toilet cleaners to retain composition on angular surfaces.
- (xiv) Abrasives - particularly for hard surface cleaning compositions. An abrasive may be deposited from the composition and mechanically agitated to provide additional cleaning. Compounds such as fumed silica may be used.
- (xv) Alkaline compounds - particularly for hard surfaces and including ammonia, amines, such as mono-, di-, and triethanolamine, morpholine and AMP regular.
- (xvi) Antimicrobials - including disinfectant, antibacterial and germicidal compounds.
- (xvii) Enzymes - including protease, amylase, lipase and cellulase
- (xviii) Hydrotropes - such as urea
- (xix) Solvents for specific soils - such as ethanol, iso-propanol, glycol ethers, N-methylpyrrolidone, white spirit, kerosene, n-paraffins, iso-paraffins, naphthene-containing solvents, ester solvents, terpenes, cycloalkanes, hydrofluorocarbon solvents.
- (xx) Chlorine, oxygen or reducing bleaching substances - such as hypochlorite, peroxygen compounds, sodium dithionite (sodium hydrosulfite) and sodium metabisulfite for use in bleachable stain removal. Such compositions will usually require the use of synthetic plastic aerosol containers.
- (xxi) Supplementary propellants such as dimethyl ether and hydrofluorocarbons.

The pH of the compositions is not critical and as mentioned previously, a toilet cleaning composition may have a very low pH, typically 1 or less. Similarly, some hard surface cleaning compositions may have a very high pH such as 13 or above.

For other cleaning purposes, the pH may be in the range of from 7 up to 11.5.

5 The compositions of the invention may be prepared in the form of a variety of cleaning compositions including textile cleaners, such as carpet cleaners and prewash cleaners; hard surface cleaners for uses such as toilets, tiles, glass, stainless steel, ovens, kitchen, bathroom surfaces; paint strippers and mildew removers.

#### Manufacture

10 To produce compositions of the invention a concentrate is formed by dissolving the water phase ingredients and then adding the oil phase ingredients with stirring. In some circumstances heating may be required. This concentrate is then filled into aerosol packages and gassed with propellant in a conventional manner.

#### EXAMPLES

15 In order to better understand the nature of the invention, the following examples, which illustrate prewash cleaning compositions, were prepared.

Note that essential components are according to the definition on page 2.

<u>EXAMPLE 1</u>	Ingredient	% w/w
	(b) Crillet 45	3.30
	(b) Monamulse DL 1273	3.30
	(b) Surfadone LP 300	5.50
	(d) Denatured Absolute Ethanol 100 AG/F3	15.40
	(c) Norpar 15	5.50
	(e) Deionised water	44.10
	(a) Butane	16.95
	(a) Propane	<u>5.95</u>
		100.00

<u>EXAMPLE 2</u>	<u>Ingredient</u>	<u>% w/w</u>
(b)	Teric LA4	11.90
(b)	Teric G12A6	1.15
	Surfadone LP300	0.50
(c)	Norpar 12	9.35
(d)	Denatured Absolute Ethanol 100AG/F3	15.00
	Light Soda Ash	0.10
	Sodium Bicarbonate (standard grade)	0.05
	Sodium citrate	0.10
	Perfume	0.20
	Sodium Lauroyl Sarcosinate (30% active)	0.70
	AMP Regular	0.20
(e)	Deionised water	40.35
(a)	Butane	15.10
(a)	Propane	<u>5.30</u>
		100.00

The pH of this example was about 11 and pressure about 65-68 psi at 25°C.

<b><u>EXAMPLE 3</u></b>	<b>Ingredient</b>	<b>% w/w</b>
(b) Teric LA4		10.90
(b) Teric G12A6		2.05
Surfadone LP300		0.50
(c) Norpar 12		9.35
(d) Denatured Absolute Ethanol 100 AG/F3		15.00
Light Soda Ash		0.10
Sodium Bicarbonate (standard grade)		0.05
Sodium Citrate		0.10
Perfume		0.20
Sodium Nitrite		0.20
(e) Deionised Water		41.15
(a) Butane		15.10
(a) Propane		<u>5.30</u>
		<u>100.00</u>

The pH of this example was about 11 and pressure about 65-68 psi at 25°C.

<b><u>EXAMPLE 4</u></b>	<b>Ingredient</b>	<b>% w/w</b>
(b) Teric LA4		10.73
(b) Teric G12A6		2.25
Surfadone LP300		0.50
(c) Norpar 12		9.35
(d) Denatured Absolute Ethanol 100 AG/F3		15.00
Light Soda Ash		0.10
Sodium Bicarbonate (standard grade)		0.05
Sodium Citrate		0.10
Perfume		0.20
Sodium Nitrite		0.20
(e) Deionised Water		41.15
(a) Butane		17.14
(a) Propane		<u>3.26</u>
		100.00

The pH of this example was about 11 and pressure about 50-51 psi at 25<sup>0</sup>C.

**EXAMPLE 5**

<b>Ingredient</b>	<b>% w/w</b>
(b) Teric LA4	9.40
(b) Teric G12A6	3.40
Surfadone LP300	0.50
(c) Norpar 12	9.35
(d) Denatured Absolute Ethanol 100 AG/F3	17.00
Light Soda Ash	0.10
AMP Regular	0.10
Sodium Citrate	0.10
DS 1986	1.10
Perfume	0.20
Sodium Lauroyl Sarcosinate (30% active)	0.35
(e) Deionised Water	38.00
(a) Butane	15.10
(a) Propane	<u>5.30</u>
	100.00

The pH of this example was about 11.5 and pressure about 65-68 psi at 25<sup>0</sup>C.



**Ingredient Availability**

- AMP Regular - Angus Chemicals (2-amino-2-methyl-propanol)  
Crillet 45 - Croda (sorbitan trioleate condensed with 20 moles ethylene oxide)
- 5 Monamulse DL1273 - Mona Industries, Inc (85% active alkanolamides and sulfosuccinate esters)  
Surfadone LP300 - ISP  
Denatured Absolute ethanol - CSR Ltd  
Norpar 15 - Exxon (mixture of predominantly C<sub>13</sub> - C<sub>14</sub> n-alkanes)
- 10 Norpar 12 - Exxon (mixture of predominantly C<sub>10</sub> - C<sub>13</sub> n-alkanes)  
Teric LA4 - ICI (straight chain synthetic C<sub>12</sub> - C<sub>15</sub> alcohol condensates with 4.5 moles of ethylene oxide)  
Teric G12A6 - ICI (straight chain synthetic C<sub>12</sub> - C<sub>15</sub> alcohol condensates with 6.0 moles of ethylene oxide)
- 15 DS1986 - ICI (Teric 12A series fatty alcohol)  
Light Soda Ash - Penrice (Sodium carbonate standard grade)  
Sodium Bicarbonate - (Penrice standard grade)  
Butane - Boral Gas (unodourised commercial butane)  
Propane - Boral Gas (unodourised commercial propane)

20 **Cleaning Performance**

The cleaning performance of examples 1 and 5 was evaluated using the following test methodology for prewash products.

1.0 **FABRIC**

White polyester/cotton 65/35

25 White cotton 100%

2.0 **WASHING CONDITIONS**

2.1 Hoover Elite 1025 top loading automatic washing machine, 12 minute wash, 2 rinses.

2.2 Wash temperature: Cold, record actual temperature

30 2.3 Detergent: standard commercial powder laundry detergent 1.5g/L.

2.4 Only test and control swatches are washed in machine, no dummy load.

2.5 Swatches are dried in tumble dryer before evaluation.

### 3.0 STAINS

#### Test Stains:

##### Grease and Oil Category

1. Sump Oil (applied to soak 80 mm circle)
- 5 2. Engine Grease (applied to soak 50 mm circle)
3. Lipstick (applied over 10x50 mm area)
4. Shoe Polish (dabbed lightly on 25 mm circle)
5. \* Synthetic Sebum (heat at 37°C, blue fabric)

##### Bleachable Category

- 10 6. Blue Biro (applied approx over 10x50 mm area)
7. Black Texta (solvent based felt pen applied over 10 x 50 mm area)
8. Red Wine (applied to soak approx 80 mm circle)

##### Proteinaceous Category

- 15 9. Grass (applied to approx 10x50 mm area)

Fabric swatches are to be washed according to washing conditions given above prior to staining.

- 20 Always prepare two sets of stains more than the number of samples to be evaluated and wash one set without prewash treatment (control swatches) and keep the other set unwashed and without prewash treatment as rating standards for no stain removal. Select swatches randomly for samples to be evaluated.

### 4.0 TIMING

Standard time between staining and prewash application is 24 hours.

- 25 4.1 Aerosols and Triggers: apply pre-wash for 1 minute before washing.
- 4.2 Soaker: Soak for 12 hours before washing.
- 4.3 Soap: Apply approx 0.5 g to each stain and scrub for approx 30 seconds before washing

### 5.0 RATING

- 30 5.1 Stains are rated on a 0-5 scale
  - 0 indicates complete removal of stain
  - 5 indicates no removal of stain
  - 0.5 units are used in rating
- 35 5.2 Stains are rated by n experienced people independently and the ratings averaged for each stain.

5.3 Stains are rated in strong "south" daylight (would be north light in the northern hemisphere). White swatches are laid flat on a dark background for rating, this procedure makes rating easier and more reproducible, especially for oil stains.

5 **6.0 TEST DESIGN**

6.1 This varies depending on the aim of the test. Extra parameters such as age of the stain or washing conditions can be varied if necessary.

6.2 An "untreated" control stain is always washed in the same load as each sample tested with prewash. A number of different stains are tested in the same wash load (along with their corresponding "untreated" controls) but only one prewash product is tested in the one washing machine load.

6.3 Wherever possible, ratings are compared only within the one set of trials.

15 \* Synthetic Sebum Formula

Component	% w/w
Palmitic acid	10.0
Stearic acid	5.0
Coconut oil	15.0
Paraffin wax	10.0
Spermaceti wax	15.0
Olive oil	20.0
Squaline	5.0
Cholesterol	5.0
Oleic acid	10.0
Linoleic acid	<u>5.0</u>
Total	100.0

**Results : First Series (n = 3)****Prewash Compositions**

<b>Soil/Fabric</b>	<b>C</b>	<b>N</b>	<b>P</b>	<b>Q</b>	<b>R</b>	<b>S</b>	<b>T</b>	<b>U</b>	<b>Example 1</b>
Engine Grease/ Cotton	5	4.83	2.83	4.67	3.00	3.00	5.00	3.17	3.33
Lipstick/Cotton	5	3.67	3.33	2.17	3.67	3.67	2.33	2.00	2.00
Lipstick/ Poly-Cotton	5	3.83	2.33	3.00	3.33	3.33	2.83	2.00	1.67
Shoe Polish/ Cotton	5	3.50	4.00	3.33	4.00	4.33	3.67	3.00	2.17
Shoe Polish/ Poly- Cotton	5	3.17	3.67	2.83	3.67	4.17	3.67	3.00	2.33
Sebum synthetic/ Cotton	5	1.33	0.17	2.00	0.17	0	1.83	0	0
Sebum synthetic/ Poly-cotton	5	1.50	0	1.17	0	0	1.50	0	0
Blue Biro/Cotton	5	4.00	2.33	1.83	2.00	2.00	2.67	1.33	0.67
Blue Biro/ Poly-cotton	5	4.33	3.83	3.33	2.67	3.00	4.50	2.33	2.17
Black Texta/ Cotton	5	4.67	5.50	4.17	4.67	4.67	4.67	5.33	3.00
Red wine/Cotton	5	2.00	2.17	2.67	2.67	3.17	2.83	2.50	1.83
Red wine/ Poly-cotton	5	1.17	1.00	1.83	2.00	2.00	2.67	1.17	1.00
Grass/Cotton	5	3.50	4.33	3.83	3.50	3.50	3.17	3.67	2.00
Grass/ Poly-cotton	5	2.83	3.00	4.00	3.50	3.00	2.50	2.83	2.50

5

Wash Temperature : 20-22°C

**Results : Second Series (n = 4)****Prewash Compositions**

5

Soil/Fabric	C	N	P	R	Example 5
Sump Oil/ Poly-cotton	5	3.88	2.13	2.50	0.63
Engine Grease/ Poly-cotton	5	4.50	2.75	2.25	1.63
Lipstick/ Poly-cotton	5	3.50	2.25	1.88	1.50

**Key : Pre-wash Compositions Used**

	C	Rating standard for no stain removal (no prewash and not washed)
	N	No pre wash (washed control)
10	P	Isoparaffin based trigger
	Q	Water based trigger
	R	Isoparaffin based aerosol
	S	White spirit based aerosol
	T	Water based protease enzyme pump spray
15	U	Naphthene based trigger

For the aerosols of the first series, samples were applied through a standard Delta MBU actuator with a 0.41 mm diameter orifice Brown Aqua Insert obtained from Precision Valve.

20

For the aerosols of the second series, samples were applied through an integrated actuator/overcap without an insert and with an orifice 0.85 mm in diameter obtained from Precision Valve.

Aerosol valves of the same specification were used in both comparisons for R, S, Example 1 and Example 5.

25

It was observed that the use of the integrated actuator/overcap delivered the composition faster to the surface as compared with the Delta actuator. This may mean that more propellant is retained with a subsequent more vigorous and longer lasting bubbling action.

In addition to outstanding cleaning performance for a water-based prewash cleaning composition, the compositions of this invention display a number of advantages over the prior art:-

- 5       - In assessing flammability, preferred compositions exhibit no burn back and do not self sustain burning. By contrast prior art hydrocarbon solvent based compositions usually self sustain burning. Further, when hydrocarbon propellant is used in combination with hydrocarbon solvent, the compositions usually burn back as well.
- 10       - Compared with the prior art solvent-based compositions, there is a significant reduction in preferred compositions in volatile organic compounds (VOC's). This is of particular importance in terms of environmental considerations.
- 15       - There is a saving in ingredient costs in preferred compositions that include ethanol as the water-miscible coupling agents as compared with conventional hydrocarbon, solvent-based compositions.
- 20       - There is also a saving in ingredient costs by replacing a proportion of conventional hydrocarbons with water.
- In preferred compositions a stable clear microemulsion of the hydrocarbon propellant is formed which obviates the need for shaking the aerosol before use.
- The bubbling action on the surface provides a visual indication to consumers of the cleaning action of the compositions.
- 25       - In preferred compositions the bubbling action is achieved in the presence of surfactants in a water-based composition without creating a foam cover.

30       It will be appreciated by persons skilled in the art that numerous variations and/or modifications may be made to the invention as shown in the specific embodiments without departing from the spirit or scope of the invention as broadly described. The present embodiments are, therefore, to be considered in all respects as illustrative and not restrictive.

Claims

1. A cleaning composition in aerosol form comprising an oil-in-water emulsion containing
- 5 (a) 2 to 60% w/w in total amount of one or more hydrocarbon propellants, wherein the propellants substantially form a part of the oil phase when the composition is formulated;
- (b) 2 to 50% w/w in total amount of one or more surfactants;
- (c) 0.1 to 30% w/w in total amount of one or more water-immiscible organic compounds;
- 10 (d) 0.5 to 40% w/w in total amount of one or more water-miscible organic coupling agents; and
- (e) 10 to 70% w/w of water;
- characterised in that sufficient of the propellant is retained in the emulsion on discharge to a surface such that the retained propellant boils to
- 15 create a sustained bubbling action in the absence of foaming on the surface.
2. The cleaning composition according to claim 1 wherein the sustained bubbling action lasts for up to 15 seconds.
3. The cleaning composition according to claim 1 wherein the sustained bubbling action lasts for up to 15 seconds followed by a
- 20 continuous, less vigorous bubbling action for up to 1 minute or more.
4. The cleaning composition according to claim 1 wherein the sustained bubbling action lasts for at least 10 seconds.
5. The cleaning composition according to any one of claims 1 to 4 wherein the concentration of the one or more propellants is from 5 to 50%
- 25 w/w.
6. The cleaning composition according to claim 5 wherein the concentration of the one or more propellants is from 10 to 30% w/w.
7. The cleaning composition according to any one of claims 1 to 6 wherein the one or more propellants are selected from the group consisting
- 30 of acetylene, methane, ethane, ethylene, propane, propene, n-butane, n-butene, iso-butane, iso-butene, pentane, pentene, iso-pentane, iso-pentene, and mixtures thereof.
8. The cleaning composition according to claim 7 wherein the one or more propellants are propane, n-butane, iso-butane, pentane, iso-pentane,
- 35 and mixtures thereof.

9. The cleaning composition according to claim 7 wherein the one or more propellants are propane, n-butane, iso-butane, and mixtures thereof.
10. The cleaning composition according to any one of claims 1 to 9 wherein the concentration of the one or more surfactants is from 5 to 25% w/w.
11. The cleaning composition according to any one of claims 1 to 10 wherein the concentration of an individual surfactant in a mixture of more than one surfactant is from 0.1 to 5% w/w.
12. The cleaning composition according to any one of claims 1 to 11 wherein the one or more surfactants are selected from the group consisting of nonionic surfactants, anionic surfactants, amphoteric surfactants and cationic surfactants.
13. The cleaning composition according to claim 12 wherein the nonionic surfactants are selected from the group consisting of sorbitan fatty acid ester ethoxylates, glycerol fatty acid ester ethoxylates, sorbitan fatty acid esters, glycerol fatty acid esters, coconut monoethanolamide ethoxylates, tall oil ethoxylates, polypropylene glycol ethoxylates, fatty acid alkanolamides, coconut mono- and diethanolamide, fatty alcohol ethoxylates and propoxylates, amine oxides, n-alkyl pyrrolidones, alkyl polysaccharides, sucrose esters and alkyl polyglycosides, alkyl phenol ethoxylates, ethoxylated castor oil, fatty acid ethoxylates, fatty amine ethoxylates, and polyglycerol fatty acid esters.
14. The cleaning composition according to claim 12 wherein the anionic surfactants are selected from the group consisting of sodium lauryl ether sulfate, triethanolamine lauryl sulphate, magnesium lauryl sulfate, sulfosuccinate esters, ammonium lauryl sulfate, alkyl sulfonates, sodium lauryl sulfate, sodium alpha olefin sulfonates, alkyl sulfates, sulfated alcohol ethoxylates, sulfated alkyl phenol ethoxylates, sodium xylene sulfonate, alkylbenzene sulphonates, triethanolamine dodecylbenzene sulfonate, sodium dodecylbenzene sulfonate, calcium dodecylbenzene sulfonate, xylene sulfonic acid, dodecylbenzene sulfonic acid, N-alkoyl sarcosinates, sodium lauroyl sarcosinate, dialkylsulfosuccinates, N-alkoyl sarcosines lauroyl sarcosine, alkyl ether carboxylates, soaps, and sodium-, potassium-, magnesium-, calcium-, alkanolamine-, and amine- soaps.



15. The cleaning composition according to claim 12 wherein the amphoteric surfactants are selected from the group consisting of betaines, n-alkyl pyrrolidones, and imidazolines.
16. The cleaning composition according to claim 12 wherein the cationic surfactants are selected from the group consisting of quaternary ammonium compounds, alkyl dimethyl benzyl ammonium chloride, dialkyl dimethyl ammonium chloride, alkyl trimethyl ammonium chloride or bromide, salts of organic or inorganic acids with fatty amines, and fatty amine ethoxylates.
17. The cleaning composition according to claim 13 or 14 comprising a mixture of nonionic and anionic surfactants.
18. The cleaning composition according to any one of claims 1 to 16 wherein the concentration of the one or more water-immiscible organic compounds is from 0.5 to 30% w/w.
19. The cleaning composition according to claim 18 wherein the concentration of the one or more water-immiscible organic compounds is from 2 to 20% w/w.
20. The cleaning composition according to any one of claims 1 to 19 wherein the one or more water-immiscible organic compounds function to suppress generation of foam on discharge of the aerosol.
21. The cleaning composition according to any one of claims 1 to 20 wherein the one or more water-immiscible organic compounds are selected from the group consisting of liquid n-paraffins, liquid iso-paraffins, cycloalkanes, naphthene-containing solvents, white spirit, kerosene, aromatic solvents, mineral turpentine, ester solvents, silicone solvents or oils, terpenes, fatty acids, paraffin waxes, linear alkyl benzene, dialkyl phthalates, C<sub>5</sub> - C<sub>11</sub> alcohols, and fatty alcohols.
22. The cleaning composition according to claim 21 wherein the liquid n-paraffins are selected from the group consisting of Norpar 12, Norpar 13, and Norpar 15.
23. The cleaning composition according to claim 21 wherein the liquid iso-paraffins are selected from the group consisting of Isopar G, Isopar H, Isopar L, Isopar M and Isopar V.
24. The cleaning composition according to claim 21 wherein the naphthene-containing solvents are selected from the group consisting of Exxsol D40, Exxsol D60, Exxsol D80, and Nappar 10.

25. The cleaning composition according to claim 21 wherein the ester solvents are alkyl acetates.
26. The cleaning composition according to claim 21 wherein the aromatic solvents are selected from the group consisting of toluene, benzene,  
5 and xylene.
27. The cleaning composition according to claim 21 wherein the silicone solvents or oils are selected from the group consisting of Dow Corning 244, 245, 344, and 345 fluids.
28. The cleaning composition according to claim 21 wherein the  
10 terpenes are selected from the group consisting of eucalyptus oil, cineole, orange oil, and limonene.
29. The cleaning composition according to claim 21 wherein the fatty amines are selected from the group consisting of soya amines, tallow amines, and cocoamines.
- 15 30. The cleaning composition according to claim 21 wherein the fatty acids are selected from the group consisting of caprylic acid, caproic acid, capric acid, lauric acid, myristic acid, palmitic acid, stearic acid, behenic acid, and oleic acid.
- 20 31. The cleaning composition according to claim 21 wherein the fatty alcohols are selected from the group consisting of octanol, dodecanol, lauryl alcohol, myristyl alcohol, cetyl alcohol, stearyl alcohol, cetostearyl alcohol, and oleyl alcohol.
32. The cleaning composition according to claim 21 wherein the one or more water-immiscible organic compounds are grease dissolving solvents.
- 25 33. The cleaning composition according to claim 21 wherein the one or more water-immiscible organic compounds are selected from liquid n-paraffins and liquid iso-paraffins.
34. The cleaning composition according to any one of claims 1 to 33 wherein the concentration of the one or more water-miscible organic  
30 coupling agents is from 5 to 30% w/w.
- 35 35. The cleaning composition according to any one of claims 1 to 34 wherein the one or more water-miscible organic coupling agents are selected from the group consisting of low molecular weight alcohols, glycol ethers, glycols, polyglycols, polypropylene glycols, polyols, low molecular weight ketones, and N-methyl pyrrolidone.

36. The cleaning composition according to claim 35 wherein the low molecular weight alcohols are selected from the group consisting of methanol, ethanol, n-propanol, iso-propanol, n-butanol, and iso-butanol.
37. The cleaning composition according to claim 36 wherein the low molecular weight alcohols are selected from ethanol and iso-propanol.
38. The cleaning composition according to claim 37 wherein the low molecular weight alcohol is ethanol.
39. The cleaning composition according to claim 35 wherein the glycol ethers are selected from the group consisting of ethylene glycol monobutyl ether, dipropylene glycol monomethyl ether, propylene glycol monomethyl ether, and diethylene glycol monobutyl ether.
40. The cleaning composition according to claim 35 wherein the glycols are selected from the group consisting of propylene glycol, hexylene glycol, and ethylene glycol.
41. The cleaning composition according to claim 35 wherein the polyglycols are selected from PEG200 and PEG6000.
42. The cleaning composition according to claim 35 wherein the polyols are selected from the group consisting of glycerol, sorbitol, pentaerythritol, and mannitol.
43. The cleaning composition according to claim 35 wherein the low molecular weight ketone is acetone.
44. The cleaning composition according to any one of claims 1 to 43 further including one or more of surfactant additives; alkaline builders; sequestering, complexing agents or water softening agents; pH control, buffering or adjusting agents; perfumes; dyes; preservatives; soil suspending or anti-redepositing agents; soil release or anti-resoiling agents; corrosion inhibitors; co-surfactants (water immiscible coupling agents); organic and/or inorganic acids; thickening agents; abrasives; alkaline compounds; antimicrobials; enzymes; hydrotropes; solvents for specific soils; chlorine, oxygen or reducing bleaching substances; and supplementary propellants.
45. The cleaning composition according to any one of claims 1 to 44 in the form of textile cleaners, carpet cleaners and prewash cleaners; hard surface cleaners for toilets, tiles, glass, stainless steel, ovens, kitchens, bathroom surfaces; paint strippers or mildew removers.

46. A method of cleaning a surface comprising applying to that surface a cleaning composition according to any one of claims 1 to 45 in a manner such that sufficient of the propellant is retained in the emulsion on discharge so that the retained propellant boils to create a sustained bubbling action in the absence of foaming on the surface.

47. A method of forming a cleaning composition according to any one of claims 1 to 45 comprising the steps of (i) dissolving the water-phase ingredients, (ii) adding the oil-phase ingredients to the dissolved water-phase ingredients with stirring to form a concentrate, (iii) adding the concentrate to an aerosol package, and (iv) gassing the concentrate with the propellant.

48. A cleaning composition in aerosol form substantially as herein described with reference to any one of the Examples.

## INTERNATIONAL SEARCH REPORT

International Application No.  
PCT/AU 96/00373

<b>A. CLASSIFICATION OF SUBJECT MATTER</b>																						
Int Cl <sup>6</sup> : C11D 17/00, 3/18																						
According to International Patent Classification (IPC) or to both national classification and IPC																						
<b>B. FIELDS SEARCHED</b>																						
Minimum documentation searched (classification system followed by classification symbols) IPC: C11D 17/00, 3/18																						
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched AU: IPC as above																						
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) DERWENT: emulsi: JAPIO : emulsi:																						
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>																						
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.																				
A	WO, 90/05774, A (IMAGINATIVE RES ASS) 31 May 1990 whole document	1-48																				
A	WO, 90/11343, A (IMAGINATIVE RES ASS) 4 October 1990 whole document	1-48																				
A	EP, 559472, A1 (UNILEVER PLC) 9 August 1993 whole document	1-48																				
A	US, 3947567, A (PHOENIX RESEARCH INC.) 30 March 1976 whole document	1-48																				
<input type="checkbox"/> Further documents are listed in the continuation of Box C <input checked="" type="checkbox"/> See patent family annex																						
<p>* Special categories of cited documents:</p> <table border="0"> <tr> <td>"A"</td> <td>document defining the general state of the art which is not considered to be of particular relevance</td> <td>"T"</td> <td>later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</td> </tr> <tr> <td>"E"</td> <td>earlier document but published on or after the international filing date</td> <td>"X"</td> <td>document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</td> </tr> <tr> <td>"L"</td> <td>document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</td> <td>"Y"</td> <td>document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</td> </tr> <tr> <td>"O"</td> <td>document referring to an oral disclosure, use, exhibition or other means</td> <td>"&amp;"</td> <td>document member of the same patent family</td> </tr> <tr> <td>"P"</td> <td>document published prior to the international filing date but later than the priority date claimed</td> <td></td> <td></td> </tr> </table>			"A"	document defining the general state of the art which is not considered to be of particular relevance	"T"	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention	"E"	earlier document but published on or after the international filing date	"X"	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone	"L"	document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y"	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art	"O"	document referring to an oral disclosure, use, exhibition or other means	"&"	document member of the same patent family	"P"	document published prior to the international filing date but later than the priority date claimed		
"A"	document defining the general state of the art which is not considered to be of particular relevance	"T"	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention																			
"E"	earlier document but published on or after the international filing date	"X"	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone																			
"L"	document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y"	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art																			
"O"	document referring to an oral disclosure, use, exhibition or other means	"&"	document member of the same patent family																			
"P"	document published prior to the international filing date but later than the priority date claimed																					
Date of the actual completion of the international search 25 August 1996		Date of mailing of the international search report 4 OCT 1996																				
Name and mailing address of the ISA/AU AUSTRALIAN INDUSTRIAL PROPERTY ORGANISATION PO BOX 200 WODEN ACT 2606 AUSTRALIA Facsimile No.: (06) 285 3929		Authorized officer J. TURNER Telephone No.: (06) 283 2071																				

**INTERNATIONAL SEARCH REPORT**

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report				Patent Family Member			
EP	559472	AU	36412/93	AU	667082	CZ	9402153
		DE	69302607	ES	2087653	GB	9204976
		HU	68651	JP	7504453	SK	1057/94
		US	5391316	WO	9318128	ZA	9301592
		GB	9217001	WO	9404639		
US	3947567	DE	1814022	GB	1257651	JP	49030909
		FR	1602979	US	3947568	US	3947566
WO	9005774	AT	140260	AU	46573/89	AU	628115
		CA	2001536	DE	68926818	EP	442968
		MX	164588	US	4931204	US	5186857
WO	9011343	US	5186857	AT	140260	AU	46573/89
		AU	628115	CA	2001536	DE	68926818
		EP	442968	MX	164588	US	4931204
END OF ANNEX							